

SAFETY DATA SHEET NOVA LONG-LIFE SATIN FINISH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name NOVA LONG-LIFE SATIN FINISH

Internal identification BN0010/SATIN

Container size 2x5L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Floor polish.

1.3. Details of the supplier of the safety data sheet

Supplier Cleenol Group Ltd

Neville House Beaumont Road Banbury

Oxon OX16 1RB

UK

Tel: +44 (0)1295 251721 sales@cleenol.co.uk

1.4. Emergency telephone number

Emergency telephone In case of a medical emergency following exposure to a chemical, call NHS Direct in England

or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

NOVA LONG-LIFE SATIN FINISH

Precautionary statements P261 Avoid breathing vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with national regulations.

Contains ROSIN, FUMARATED, POLYMER WITH GLYCEROL, AMMONIUM SALT

Detergent labelling Contains BRONOPOL (INN)

statements

Supplementary precautionary P272 Contaminated work clothing should not be allowed out of the workplace.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

POLYMERIC EMULSION 30-60%

CAS number: —

Classification

Eye Irrit. 2 - H319

MONOETHYLENE GLYCOL 1-5%

CAS number: 107-21-1 EC number: 203-473-3

Classification

Acute Tox. 4 - H302 STOT RE 2 - H373

ROSIN, FUMARATED, POLYMER WITH GLYCEROL,

1-5%

AMMONIUM SALT

CAS number: 68554-18-7

Classification

Eye Irrit. 2 - H319 Skin Sens. 1B - H317 Aquatic Chronic 4 - H413

POTASSIUM HYDROXIDE <1%

CAS number: 1310-58-3 EC number: 215-181-3 REACH registration number: 01-

2119487136-33-XXXX

Classification

Met. Corr. 1 - H290 Acute Tox. 4 - H302 Skin Corr. 1A - H314 Eye Dam. 1 - H318

NOVA LONG-LIFE SATIN FINISH

BRONOPOL (INN) <1%

CAS number: 52-51-7 EC number: 200-143-0 REACH registration number: 01-

2119980938-15-XXXX

M factor (Acute) = 10

Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 3 - H331 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335 Aquatic Acute 1 - H400 Aquatic Chronic 2 - H411

ETHANE-1,2-DIOL <1%

CAS number: 107-21-1 EC number: 203-473-3

Classification

Acute Tox. 4 - H302

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

In the event of any sensitisation symptoms developing, ensure further exposure is avoided.

Ingestion Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Keep

affected person under observation. Get medical attention if symptoms are severe or persist.

Get medical attention if a large quantity has been ingested.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water.

Eye contact Rinse cautiously with water for several minutes. Remove any contact lenses and open eyelids

wide apart. Continue to rinse. Get medical attention if symptoms are severe or persist.

4.2. Most important symptoms and effects, both acute and delayed

General information May produce an allergic reaction.

Inhalation May cause respiratory irritation.

Ingestion No adverse effects known. May be harmful if swallowed.

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media
Use fire-extinguishing media suitable for the surrounding fire.

NOVA LONG-LIFE SATIN FINISH

Unsuitable extinguishing

media

None known.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials. Firefighter's clothing

conforming to European standard EN469 (including helmets, protective boots and gloves) will

provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and prolonged skin contact. Take care as floors and other surfaces

may become slippery. Do not touch or walk into spilled material.

6.2. Environmental precautions

Environmental precautions No negative effects on the aquatic environment are known. No specific requirements are

anticipated under normal conditions of use.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large

Spillages: Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Do not breathe spray. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated

areas.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container. Keep container tightly sealed when not in use. Keep away

from heat. Store at temperatures between 0°C and 40°C.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2. Refer to Product Use Guide

(PUG) for further information.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

POTASSIUM HYDROXIDE

Long-term exposure limit (8-hour TWA): WEL Short-term exposure limit (15-minute): WEL 2 mg/m³

ETHANE-1,2-DIOL

NOVA LONG-LIFE SATIN FINISH

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

Sk

Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour

Sk

WEL = Workplace Exposure Limit. Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

Hand protection For users with sensitive skin, it is recommended that suitable protective gloves are worn. It is

recommended that gloves are made of the following material: Rubber (natural, latex). Nitrile rubber. To protect hands from chemicals, gloves should comply with European Standard

EN374.

Hygiene measures Wash contaminated skin thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Opaque liquid.

Colour Beige.

Odour Slight pungent. Ammonia.

pH (concentrated solution): 8.5 - 9.0

Initial boiling point and range Not determined.

Flash point Not applicable.

Relative density 1.03 - 1.04 @ 20°C

Solubility(ies) Miscible with water.

Auto-ignition temperature Not applicable.

Decomposition Temperature Not determined.

Viscosity Non-viscous.

Explosive properties Not applicable.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

Refractive index 21 - 24

Volatile organic compound See SECTION 3: Composition/information on ingredients.

NOVA LONG-LIFE SATIN FINISH

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Information given is based on data of the components and of similar products.

Acute toxicity - oral

ATE oral (mg/kg) 39,062.5

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Medical considerations Skin disorders and allergies. Pre-existing eye problems.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity The product is not believed to present a hazard due to its physical nature.

12.2. Persistence and degradability

Persistence and degradability Moderately biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product contains substances which are water-soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

NOVA LONG-LIFE SATIN FINISH

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

contractor.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

NOVA LONG-LIFE SATIN FINISH

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products (as amended). Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Issued by Regulatory Chemist

Revision date 02/03/2021

Revision 14

Supersedes date 25/02/2021

SDS number 10544

Hazard statements in full H290 May be corrosive to metals.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure if

swallowed.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.